

View Online at <https://aerobasegroup.com/nsn/5950-01-311-5375>

Reliability Indicator:

Not established

Overall Length:

5.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.485 inches single mounting facility single center group and 3.515 inches single mounting facility single center group

Overall Width:

4.437 inches

Mounting Hole Diameter:

0.260 inches single group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Height:

5.000 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Winding Operating Current:

25.0 milliamperes dc single component 1st secondary

Winding Power Rating:

43.24 volts-amperes single component 2nd secondary

Winding Operating Voltage:

8.70 dc volts single component 2nd secondary and 9.40 dc volts single component 2nd secondary

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0