

View Online at <https://aerobasegroup.com/nsn/5950-01-311-5377>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.781 inches single mounting facility single center group and 2.843 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.218 inches single mounting facility single center group and 2.281 inches single mounting facility single center group

Mounting Hole Diameter:

0.245 inches single group and 0.255 inches single group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.437 inches

Body Width:

2.875 inches

Body Height:

2.875 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.0 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac pounds per hour wet single component single primary

Test Data Document:

96696-a-601808 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0