

View Online at <https://aerobasegroup.com/nsn/5950-01-311-9275>

Reliability Indicator:

Not established

Overall Length:

8.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.120 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.500 inches single mounting facility single center group

Overall Height:

5.620 inches

Overall Width:

5.500 inches

Mounting Slot Width:

0.280 inches single group

Frequency Rating:

59.0 hertz single component and 61.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta and delta-wye

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Maximum Operating Temp:

50.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Winding Operating Current:

3.0 amperes dc single component 1st secondary

Winding Operating Voltage:

9.50 dc volts single component 2nd secondary and 10.50 dc volts single component 2nd secondary

Special Features:

1 primary winding; 8 secondary windings; all secondary windings voltage and currents rectified

Terminal Type And Quantity:

30 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0