

View Online at <https://aerobasegroup.com/nsn/5950-01-311-9275>

**Reliability Indicator:**

Not established

**Overall Length:**

8.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.120 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.500 inches single mounting facility single center group

**Overall Height:**

5.620 inches

**Overall Width:**

5.500 inches

**Mounting Slot Width:**

0.280 inches single group

**Frequency Rating:**

59.0 hertz single component and 61.0 hertz single component

**Input-output Phase Relationship:**

Three phase to single phase single component and three phase to three phase single component

**Transformer Winding Connection Type:**

Delta-delta and delta-wye

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Maximum Operating Temp:**

50.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and slot single group

**Winding Function And Quantity:**

1 primary single component and 8 secondary single component

**Winding Operating Current:**

3.0 amperes dc single component 1st secondary

**Winding Operating Voltage:**

9.50 dc volts single component 2nd secondary and 10.50 dc volts single component 2nd secondary

**Special Features:**

1 primary winding; 8 secondary windings; all secondary windings voltage and currents rectified

**Terminal Type And Quantity:**

30 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0