

View Online at <https://aerobasegroup.com/nsn/5950-01-311-9941>

Reliability Indicator:

Not established

Overall Length:

Between 0.780 inches and 0.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.585 inches single mounting facility single center group and 0.615 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.385 inches single mounting facility single center group and 0.415 inches single mounting facility single center group

Overall Height:

Between 0.605 inches and 0.625 inches

Overall Width:

Between 0.575 inches and 0.595 inches

Frequency Rating:

8.0 kilohertz single component and 160.0 kilohertz single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Winding Shielding Method:

Core grounded and brought out to terminal single component and inclosure grounded single component

Maximum Operating Temp:

71.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0