

View Online at <https://aerobasegroup.com/nsn/5950-01-311-9942>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 0.780 inches and 0.800 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.585 inches single mounting facility single center group and 0.615 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.385 inches single mounting facility single center group and 0.415 inches single mounting facility single center group

**Overall Height:**

Between 0.605 inches and 0.625 inches

**Overall Width:**

Between 0.575 inches and 0.595 inches

**Frequency Rating:**

8.0 kilohertz single component and 160.0 kilohertz single component

**Primary To Secondary Turn Ratio:**

1 to 6 single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Maximum Operating Temp:**

71.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Features Provided:**

Tinned wire leads

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0