# NSN 5950-01-311-9946

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-311-9946

## Reliability Indicator:

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.980 inches single mounting facility single center group and 3.020 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

3.480 inches single mounting facility single center group and 3.520 inches single mounting facility single center group

## Mounting Hole Diameter:

0.264 inches single group

## Frequency Rating:

55.0 hertz single component and 65.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

## Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

## Body Length:

Between 8.720 inches and 8.780 inches

#### **Body Width:**

Between 2.710 inches and 2.770 inches

#### **Body Height:**

2.520 inches

## Maximum Operating Temp:

70.0 degrees celsius

#### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

6 single group

### **Mounting Method:**

Flange single group and unthreaded hole single group

# Winding Function And Quantity:

1 primary single component and 1 secondary single component

# Winding Operating Current:

0.7 amperes ac single component single secondary

# Winding Operating Voltage:

115.00 ac volts single component single secondary

# Terminal Type And Quantity:

1 connector, receptacle and 2 turret

Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5950-01-311-9946

Power Transformer - Page 2 of 2

**Fiig:** A058b0

