

View Online at <https://aerobasegroup.com/nsn/5950-01-311-9946>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.980 inches single mounting facility single center group and 3.020 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.480 inches single mounting facility single center group and 3.520 inches single mounting facility single center group

Mounting Hole Diameter:

0.264 inches single group

Frequency Rating:

55.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

Between 8.720 inches and 8.780 inches

Body Width:

Between 2.710 inches and 2.770 inches

Body Height:

2.520 inches

Maximum Operating Temp:

70.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

0.7 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single secondary

Terminal Type And Quantity:

1 connector, receptacle and 2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0