

View Online at <https://aerobasegroup.com/nsn/5950-01-312-4650>

Reliability Indicator:

Not established

Overall Length:

3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Overall Height:

1.683 inches

Overall Width:

3.125 inches

Mounting Hole Diameter:

0.218 inches single group

Frequency Rating:

47.5 hertz single component and 444.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

End Application:

Nimitz class cvn, arleigh burke class ddg, los angeles class ssn (688), sturgeon class ssn (637), virginia class cgn (41), forrestal class cv, kidd class ddg, spruance class dd (963), ticonderoga class cg (47)

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

3.3 amperes dc single component 1st secondary

Winding Power Rating:

6.4 volts-amperes single component 4th secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

5.90 dc volts single component 2nd secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0