

View Online at <https://aerobasegroup.com/nsn/5950-01-312-6742>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

10.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

12.000 inches single mounting facility single center group

Overall Height:

20.000 inches

Mounting Hole Diameter:

0.562 inches single group

Mounting Slot Width:

0.562 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

25.0 kilovolt-ampere single component

Body Length:

15.000 inches

Body Width:

13.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

55.6 amperes ac single component single primary

Winding Operating Voltage:

405.00 ac volts single component single primary and 416.25 ac volts single component single primary and 427.50 ac volts single component single primary and 438.75 ac volts single component single primary and 450.00 ac volts single component single primary and 461.25 ac volts single component single primary and 472.50 ac volts single component single primary

Terminal Type And Quantity:

14 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0