

View Online at <https://aerobasegroup.com/nsn/5950-01-313-2119>

**Reliability Indicator:**

Not established

**Inductance Rating:**

3.30 microhenries single component single winding

**Coil Form Type:**

Solid single component

**Core Construction:**

Powdered single component

**Body Length:**

Between 0.365 inches and 0.385 inches

**Body Outside Diameter:**

Between 0.146 inches and 0.166 inches

**Maximum Operating Temp:**

125.0 degrees celsius

**End Application:**

Landing craft air cushion (lcac); kidd class ddg; spruance class dd (963); nimitz class cvn; ticonderoga class cg (47); engine, aircraft  
tf33-pw-102 (c-135e, ec-135h/k/p); oliver perry class ffg; arleigh burke class ddg; forrestal class cv

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Rating Method:**

Electrical single component single winding

**Features Provided:**

Tinned wire leads

**Winding Operating Current:**

300.0 milliamperes dc single component single winding

**Dc Resistance Rating In Ohms:**

2.000 single component single winding

**Quality Factor:**

33 single component single winding

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0