

View Online at <https://aerobasegroup.com/nsn/5950-01-313-3918>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant and salt spray resistant and vibration resistant

Overall Length:

Between 6.615 inches and 6.635 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Overall Height:

Between 2.740 inches and 2.760 inches

Overall Width:

Between 3.990 inches and 4.010 inches

Mounting Hole Diameter:

0.171 inches single group and 0.175 inches single group

Inductance Type:

Fixed

Inductance Rating:

2500.00 microhenries single component single winding

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

5 single group

Mounting Method:

Flange single group and unthreaded hole single group

Rating Method:

Electrical single component single winding

Features Provided:

Tinned wire leads and w/overload protection

Winding Operating Current:

15.0 amperes ac single component single winding

Dc Resistance Rating In Ohms:

0.089 single component single winding

Terminal Type And Quantity:

2 wire lead w/lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0