

View Online at <https://aerobasegroup.com/nsn/5950-01-314-4985>

**Reliability Indicator:**

Not established

**Frequency Rating:**

20.0 kilohertz single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

1.085 inches

**Body Outside Diameter:**

Between 2.110 inches and 2.140 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

1 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Thread Size:**

0.112 inches single group

**Dc Resistance Rating In Ohms:**

0.1242 single component 4th secondary

**Special Features:**

One primary winding and five secondary windings; third, fourth, and fifth secondaries center tapped

**Test Data Document:**

95266-310-18188-02 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

13 pin and 4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0