

View Online at <https://aerobasegroup.com/nsn/5950-01-314-4988>

**Reliability Indicator:**

Not established

**Turn Quantity:**

24 single component 3rd winding

**Inductance Type:**

Swinging

**Inductance Rating:**

570.00 microhenries single component all winding and 600.00 microhenries single component all winding

**Frequency Rating:**

10.0 kilohertz single component

**Body Length:**

1.735 inches

**Body Outside Diameter:**

Between 2.590 inches and 2.610 inches

**Maximum Operating Temp:**

155.0 degrees celsius

**Mounting Bolt Circle Diameter:**

1.990 inches single mounting facility single center group and 2.010 inches single mounting facility single center group

**Winding Quantity:**

4 single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

3 single group

**Mounting Method:**

Threaded stud single group

**Rating Method:**

Electrical single component all winding

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

20.0 amperes dc single component all winding

**Dc Resistance Rating In Ohms:**

0.029 single component 3rd winding

**Special Features:**

All windings internally shielded

**Test Data Document:**

95266-315-18191-04 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0