## NSN 5950-01-314-4988

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-314-4988

**Reliability Indicator:** 

Not established

**Turn Quantity:** 

24 single component 3rd winding

**Inductance Type:** 

Swinging

**Inductance Rating:** 

570.00 microhenries single component all winding and 600.00 microhenries single component all winding

**Frequency Rating:** 

10.0 kilohertz single component

**Body Length:** 

1.735 inches

**Body Outside Diameter:** 

Between 2.590 inches and 2.610 inches

**Maximum Operating Temp:** 

155.0 degrees celsius

**Mounting Bolt Circle Diameter:** 

1.990 inches single mounting facility single center group and 2.010 inches single mounting facility single center group

**Winding Quantity:** 

4 single component

**Inclosure Type:** 

Fully enclosed

**Mounting Facility Quantity:** 

3 single group

**Mounting Method:** 

Threaded stud single group

**Rating Method:** 

Electrical single component all winding

Thread Size:

0.138 inches single group

Winding Operating Current:

20.0 amperes dc single component all winding

Dc Resistance Rating In Ohms:

0.029 single component 3rd winding

**Special Features:** 

All windings internally shielded

**Test Data Document:** 

95266-315-18191-04 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:** 

Unc single group

**Terminal Type And Quantity:** 

8 wire lead

## NSN 5950-01-314-4988

Reactor - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0