

View Online at <https://aerobasegroup.com/nsn/5950-01-314-6384>

Reliability Indicator:

Not established

Overall Length:

4.870 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.620 inches single mounting facility single center group

Overall Height:

4.000 inches

Overall Width:

4.500 inches

Mounting Slot Width:

0.300 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

20.0 amperes dc single component 2nd secondary

Winding Operating Voltage:

19.00 dc volts single component 1st secondary

Special Features:

Secondary output voltages and currents are rectified

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0