NSN 5950-01-314-6384

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-314-6384

| Reliability indicator: |
|---|
| Not established |
| Overall Length: |
| 4.870 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.620 inches single mounting facility single center group |
| Overall Height: |
| 4.000 inches |
| Overall Width: |
| 4.500 inches |
| Mounting Slot Width: |
| 0.300 inches single group |
| Frequency Rating: |
| 50.0 hertz single component and 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 2 primary single component and 2 secondary single component |
| Winding Operating Current: |
| 20.0 amperes dc single component 2nd secondary |
| Winding Operating Voltage: |
| 19.00 dc volts single component 1st secondary |
| Special Features: |
| Secondary output voltages and currents are rectified |
| Terminal Type And Quantity: |
| 11 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5950-01-314-6384

Power Transformer - Page 2 of 2



Fiig:

A058b0