# NSN 5950-01-315-8118

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-315-8118

# **Reliability Indicator:**

Not established

## **Hazardous Locations/environmental Protection:**

Salt spray proof and vibration resistant

# **Overall Length:**

1.600 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility single center group

# **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.000 inches single mounting facility single center group

## **Overall Height:**

1.820 inches

#### **Overall Width:**

1.370 inches

# **Inductance Rating:**

1.00 millihenries single component single primary

# **Frequency Rating:**

15.75 kilohertz single component

# **Primary To Secondary Turn Ratio:**

1 to 1 single component

# **Maximum Operating Temp:**

85.0 degrees celsius

# **End Application:**

7042-01-252-8065, computer

# **Inclosure Type:**

Fully enclosed

# **Mounting Facility Quantity:**

2 single group

### **Mounting Method:**

Threaded hole single group

# **Winding Function And Quantity:**

1 primary single component and 3 secondary single component

# **Features Provided:**

Tinned wire leads

# Thread Size:

0.112 inches single group

# Dc Resistance Rating In Ohms:

85.000 single component single primary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

8 wire lead

# NSN 5950-01-315-8118

Pulse Transformer - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0