

View Online at <https://aerobasegroup.com/nsn/5950-01-316-0979>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Inductance Type:

Fixed

Inductance Rating:

3.75 millihenries single component all winding

Frequency Rating:

10.0 kilohertz single component

Body Length:

0.340 inches

Overall Diameter:

0.500 inches

Maximum Operating Temp:

130.0 degrees celsius

Mounting Bolt Circle Diameter:

0.340 inches single mounting facility single center group and 0.360 inches single mounting facility single center group

Winding Quantity:

2 single component

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component all winding

Winding Operating Current:

240.0 milliamperes dc single component all winding

Dc Resistance Rating In Ohms:

5.500 single component all winding

Special Features:

Magnetically shielded

Test Data Document:

81349-mil-prf-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 wire lead

Specification Data:

81349-mil-prf-27/356 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0

Mil-std (military Standard):

Mil-prf-27 spec.