NSN 5950-01-316-5908

Current Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-316-5908 |
|--|
| Reliability Indicator: |
| Not established |
| Mounting Hole Diameter: |
| 0.141 inches single group and 0.171 inches single group |
| Frequency Rating: |
| 40.0 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| Between 1.530 inches and 1.590 inches |
| Body Width: |
| 0.800 inches |
| Body Height: |
| 1.500 inches |
| Maximum Operating Temp: |
| 130.0 degrees celsius |
| Distance Between Mounting Facility Centers: |
| 1.110 inches single mounting facility single center group and 1.140 inches single mounting facility single center group |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 secondary single component |
| Winding Operating Current: |
| 14.1 amperes ac single component single primary |
| Winding Operating Voltage: |
| 1.20 ac volts single component single secondary |
| Special Features: |
| Primary rated but not included |
| Test Data Document: |
| 24039-118045 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-01-316-5908Current Transformer - Page 2 of 2



Fiig:

A058b0