NSN 5950-01-316-5908

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-316-5908
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.141 inches single group and 0.171 inches single group
Frequency Rating:
40.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
Between 1.530 inches and 1.590 inches
Body Width:
0.800 inches
Body Height:
1.500 inches
Maximum Operating Temp:
130.0 degrees celsius
Distance Between Mounting Facility Centers:
1.110 inches single mounting facility single center group and 1.140 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 secondary single component
Winding Operating Current:
14.1 amperes ac single component single primary
Winding Operating Voltage:
1.20 ac volts single component single secondary
Special Features:
Primary rated but not included
Test Data Document:
24039-118045 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5950-01-316-5908Current Transformer - Page 2 of 2



Fiig:

A058b0