

View Online at <https://aerobasegroup.com/nsn/5950-01-316-5914>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.485 inches single mounting facility single center group and 5.515 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.985 inches single mounting facility single center group and 3.015 inches single mounting facility single center group

Mounting Hole Diameter:

0.216 inches single group and 0.226 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.200 inches

Body Width:

3.840 inches

Body Height:

5.300 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

65.0 milliamperes ac single component single primary

Winding Power Rating:

28.6 volts-amperes single component single primary

Winding Operating Voltage:

440.00 ac volts single component single primary

Test Data Document:

24039-118134 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 banana plug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0