NSN 5950-01-316-8073

Reactor - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5950-01-316-8073
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Mounting Hole Diameter:
0.250 inches single group
Inductance Type:
Swinging
Inductance Rating:
46.80 microhenries single component single winding and 57.20 microhenries single component single winding
Frequency Rating:
60.0 hertz single component
Body Length:
0.700 inches
Body Outside Diameter:
1.350 inches
Maximum Operating Temp:
75.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
1 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component single winding
Winding Conductor Size:
0.05082 inches american wire gage single component single winding
Winding Operating Current:
5.4 amperes ac single component single winding
Dc Resistance Rating In Ohms:
0.032 single component single winding
Test Data Document:
24039-118144 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 wire hook
Shelf Life:
N/a
Unit Of Measure:

NSN 5950-01-316-8073

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0