# NSN 5950-01-316-8075

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-316-8075

# **Reliability Indicator:**

Not established

### Mounting Hole Diameter:

0.146 inches single group and 0.166 inches single group

## Inductance Type:

Fixed

#### Inductance Rating:

320.00 microhenries single component single winding

#### **Frequency Rating:**

10.0 kilohertz single component

#### Body Length:

Between 0.500 inches and 0.626 inches

#### **Body Outside Diameter:**

Between 1.158 inches and 1.218 inches

#### Maximum Operating Temp:

#### 130.0 degrees celsius

Winding Quantity:

1 single component

### Inclosure Type:

Fully enclosed

### Mounting Facility Quantity:

1 single group

### Mounting Method:

Unthreaded hole single group

#### **Rating Method:**

Electrical single component single winding

#### Winding Operating Current:

3.75 amperes dc single component single winding

#### Dc Resistance Rating In Ohms:

0.130 single component single winding

#### **Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

2 pin

#### **Specification Data:**

81349-mil-t-27/288 government specification

#### Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

# NSN 5950-01-316-8075

Reactor - Page 2 of 2

Fiig: A058b0

