

View Online at <https://aerobasegroup.com/nsn/5950-01-316-8076>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Mounting Hole Diameter:

0.187 inches single group

Frequency Rating:

48.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Length:

3.812 inches

Body Width:

2.937 inches

Body Height:

3.187 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

39.90 ac volts single component single secondary and 60.20 ac volts single component single secondary and 71.10 ac volts single component single secondary and 82.00 ac volts single component single secondary and 121.90 ac volts single component single secondary and 161.80 ac volts single component single secondary

Terminal Type And Quantity:

13 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0