

View Online at <https://aerobasegroup.com/nsn/5950-01-317-1886>

**Reliability Indicator:**

Not established

**Mounting Hole Diameter:**

0.128 inches single group

**Inductance Rating:**

50.00 microhenries single component single secondary and 60.00 microhenries single component single secondary

**Frequency Rating:**

19.0 kilohertz single component and 21.0 kilohertz single component

**Primary To Secondary Turn Ratio:**

1 to 1 single component

**Body Length:**

0.600 inches

**Body Outside Diameter:**

1.000 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

1 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Features Provided:**

Tinned wire leads

**Winding Operating Current:**

5.0 amperes ac single component single secondary

**Dc Resistance Rating In Ohms:**

0.050 single component single secondary

**Winding Operating Voltage:**

5.00 ac volts single component single secondary

**Test Data Document:**

99696-3191419-102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

4 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0