

View Online at <https://aerobasegroup.com/nsn/5950-01-317-1886>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.128 inches single group

Inductance Rating:

50.00 microhenries single component single secondary and 60.00 microhenries single component single secondary

Frequency Rating:

19.0 kilohertz single component and 21.0 kilohertz single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Body Length:

0.600 inches

Body Outside Diameter:

1.000 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

5.0 amperes ac single component single secondary

Dc Resistance Rating In Ohms:

0.050 single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single secondary

Test Data Document:

99696-3191419-102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0