

View Online at <https://aerobasegroup.com/nsn/5950-01-317-1888>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.900 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.600 inches single mounting facility single center group

**Frequency Rating:**

19.0 kilohertz single component and 21.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

2.500 inches

**Body Width:**

2.000 inches

**Body Height:**

1.250 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.112 inches single group

**Winding Operating Current:**

3.54 amperes ac single component single primary

**Winding Operating Voltage:**

63.63 ac volts single component single primary

**Test Data Document:**

99696-3191419-104 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 turret and 3 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0