

View Online at <https://aerobasegroup.com/nsn/5950-01-317-1888>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.900 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.600 inches single mounting facility single center group

Frequency Rating:

19.0 kilohertz single component and 21.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.500 inches

Body Width:

2.000 inches

Body Height:

1.250 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

3.54 amperes ac single component single primary

Winding Operating Voltage:

63.63 ac volts single component single primary

Test Data Document:

99696-3191419-104 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret and 3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0