

View Online at <https://aerobasegroup.com/nsn/5950-01-317-3101>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.308 inches single mounting facility single center group and 2.328 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.365 inches single mounting facility single center group and 2.385 inches single mounting facility single center group

Mounting Hole Diameter:

0.271 inches single group and 0.276 inches single group

Frequency Rating:

20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Length:

3.600 inches

Body Width:

2.775 inches

Body Height:

2.035 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component and 1 tertiary single component

Winding Operating Current:

6.43 amperes ac single component 4th secondary

Winding Power Rating:

59.73 volts-amperes single component 3rd secondary

Winding Operating Voltage:

9.05 ac volts single component 2nd secondary

Special Features:

One primary winding; six secondary windings; terminals 23 and 24 split for dual connection; tertiary winding tied to the fourth secondary winding

Test Data Document:

82577-h940081 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 bus (bar) conductor and 22 pin and 2 ribbon

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0