## NSN 5950-01-317-3886



Reactor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5950-01-317-3886 **Reliability Indicator:** Not established **Inductance Type:** Fixed **Inductance Rating:** 25.00 microhenries single component all winding Frequency Rating: 10.0 kilohertz single component **Body Length:** 0.500 inches **Body Outside Diameter:** 0.800 inches **Maximum Operating Temp:** 130.0 degrees celsius **Mounting Bolt Circle Diameter:** 0.550 inches single mounting facility single center group and 0.570 inches single mounting facility single center group Winding Quantity: 2 single component **Inclosure Type:** Fully enclosed **Mounting Method:** Terminal single group **Rating Method:** Electrical single component all winding **Winding Operating Current:** 3.08 amperes dc single component all winding Dc Resistance Rating In Ohms: 0.035 single component all winding **Test Data Document:** 81349-mil-prf-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 4 wire lead **Specification Data:** 81349-mil-prf-27/356 government specification Shelf Life: N/a **Unit Of Measure:** 

Fiig: A058b0

No

**Demilitarization:** 

## NSN 5950-01-317-3886

Reactor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-27 spec.