

View Online at <https://aerobasegroup.com/nsn/5950-01-317-7726>

Reliability Indicator:

Not established

Overall Length:

2.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.240 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group

Overall Height:

Between 1.970 inches and 2.000 inches

Overall Width:

2.300 inches

Mounting Slot Width:

0.196 inches single group

Frequency Rating:

80.0 hertz single component and 120.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

160.0 volt-ampere single component

Maximum Operating Temp:

85.0 degrees celsius

End Application:

Nuclear power plants

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

9.1 amperes ac single component single secondary

Winding Operating Voltage:

44.54 ac volts single component single primary

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo4231

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0