NSN 5950-01-317-8645

Reactor - Page 1 of 2

4 single component all winding

Reliability Indicator:

Not established

Overall Length:

2.700 inches

Turn Quantity:

Overall Height: 1.720 inches Overall Width: 0.640 inches



View Online at https://aerobasegroup.com/nsn/5950-01-317-8645

| Mounting Hole Diameter: |
|---|
| 0.188 inches single group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 100.00 microhenries single component all winding |
| Frequency Rating: |
| 60.0 hertz single component |
| Maximum Operating Temp: |
| 100.0 degrees celsius |
| Distance Between Mounting Facility Centers: |
| 2.400 inches single mounting facility single center group |
| Winding Quantity: |
| 3 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Rating Method: |
| Electrical single component all winding and winding turns single component all winding |
| Features Provided: |
| Tinned wire leads |
| Winding Conductor Size: |
| 0.03196 inches american wire gage single component all winding |
| Dc Resistance Rating In Ohms: |
| 0.007 single component all winding |
| Criticality Code Justification: |
| Zzzy |
| Special Features: |
| Item must comply with requirements of defense supply center columbus production standard no. Lo4232 |
| |
| |
| |

NSN 5950-01-317-8645

Reactor - Page 2 of 2



| Terminal | Type | And | Quantity: |
|-----------------|-------------|-----|-----------|
|-----------------|-------------|-----|-----------|

6 pin

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

| Shelf L | _ife: |
|---------|-------|
| N/a | |

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0