

View Online at <https://aerobasegroup.com/nsn/5950-01-319-2920>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.750 inches

Overall Diameter:

2.000 inches

Maximum Operating Temp:

130.0 degrees celsius

Mounting Bolt Circle Diameter:

1.562 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

3 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Thread Size:

0.164 inches single group

Winding Operating Current:

961.0 milliamperes ac single component single secondary

Winding Operating Voltage:

78.00 ac volts single component single secondary

Test Data Document:

88818-c504000202 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0