NSN 5950-01-319-4126

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-319-4126

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.990 inches single mounting facility single center group and 6.010 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

Mounting Hole Diameter:

0.271 inches single group and 0.291 inches single group

Inductance Type:

Fixed

Inductance Rating:

28.00 microhenries single component single winding

Frequency Rating:

120.0 hertz single component

Body Length:

Between 6.600 inches and 6.660 inches

Body Width:

Between 4.590 inches and 4.650 inches

Body Height:

Between 3.910 inches and 3.970 inches

Maximum Operating Temp:

65.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding

Winding Operating Current:

10.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.220 single component single winding

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

NSN 5950-01-319-4126

Reactor - Page 2 of 2



ı	1	n	iŧ	1	: N/	lea			_	
ı	u	n	IT	OI	١V	ıea	เรเ	JI	е	:

--

Demilitarization:

No

Fiig:

A058b0