

View Online at <https://aerobasegroup.com/nsn/5950-01-320-3609>

Reliability Indicator:

Not established

Impedance Rating In Ohms:

100.0 single component single secondary

Frequency Rating:

12.0 kilohertz single component and 2.3 megahertz single component

Primary To Secondary Turn Ratio:

4 to 4 to 1 single component

Body Length:

0.375 inches

Body Outside Diameter:

0.375 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Features Provided:

Color coded lead and tinned wire leads

Dc Resistance Rating In Ohms:

4.400 single component 2nd primary

Winding Operating Voltage:

7.00 ac volts single component single secondary

Test Data Document:

81349-mil-t-21038 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 wire lead

Specification Data:

81349-mil-t-21038/11 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0