NSN 5950-01-320-3930

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-320-3930

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
7.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
5.000 inches single mounting facility single center group
Mounting Hole Diameter:
0.406 inches single group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Transformer Power Rating:
1.3 kilovolt-ampere single component
Body Length:
9.250 inches
Body Width:
6.844 inches
Body Height:
7.438 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
Mounting Facility Quantity: 4 single group
4 single group
4 single group Mounting Method:
4 single group Mounting Method: Unthreaded hole single group
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity:
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current:
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary Winding Operating Voltage:
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary Winding Operating Voltage: 60.00 ac volts single component 1st secondary and 65.00 ac volts single component 1st secondary
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary Winding Operating Voltage: 60.00 ac volts single component 1st secondary and 65.00 ac volts single component 1st secondary Terminal Type And Quantity:
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary Winding Operating Voltage: 60.00 ac volts single component 1st secondary and 65.00 ac volts single component 1st secondary Terminal Type And Quantity: 7 solder stud
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary Winding Operating Voltage: 60.00 ac volts single component 1st secondary and 65.00 ac volts single component 1st secondary Terminal Type And Quantity: 7 solder stud Shelf Life:
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary Winding Operating Voltage: 60.00 ac volts single component 1st secondary and 65.00 ac volts single component 1st secondary Terminal Type And Quantity: 7 solder stud Shelf Life: N/a
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary Winding Operating Voltage: 60.00 ac volts single component 1st secondary and 65.00 ac volts single component 1st secondary Terminal Type And Quantity: 7 solder stud Shelf Life: N/a
4 single group Mounting Method: Unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 7.0 amperes ac single component 2nd secondary Winding Operating Voltage: 60.00 ac volts single component 1st secondary and 65.00 ac volts single component 1st secondary Terminal Type And Quantity: 7 solder stud Shelf Life: N/a Unit Of Measure:

A058b0