NSN 5950-01-320-6409

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-320-6409

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 2.960 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.250 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.500 inches single mounting facility single center group |
| Overall Height: |
| 4.330 inches |
| Overall Width: |
| 2.060 inches |
| Inductance Rating: |
| 7.00 millihenries single component single winding |
| End Application: |
| Milstar |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Operating Current: |
| 5.0 amperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.500 single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 2 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5950-01-320-6409

Reactor - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

