

View Online at <https://aerobasegroup.com/nsn/5950-01-320-9754>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Impedance Rating In Ohms:

150.0 single component single primary

Frequency Rating:

5.0 kilohertz single component

Maximum Transformer Power Rating:

110.0 milliwatts single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Body Length:

0.500 inches

Overall Diameter:

Between 0.490 inches and 0.510 inches

Maximum Operating Temp:

130.0 degrees celsius

Mounting Bolt Circle Diameter:

0.600 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

8.0 milliamperes dc single component single primary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

7 wire lead

Specification Data:

81349-mil-t-27/358 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0