

View Online at <https://aerobasegroup.com/nsn/5950-01-321-1902>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Frequency Rating:

1.0 kilohertz single component and 100.0 kilohertz single component

Winding Shielding Method:

Internal shield grounded to terminal single component

Body Length:

0.510 inches

Overall Diameter:

0.525 inches

Maximum Operating Temp:

105.0 degrees celsius

End Application:

Central office, telephone auto

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

150.0 milliamperes dc single component single secondary

Dc Resistance Rating In Ohms:

35.000 single component single primary

Criticality Code Justification:

Feat

Winding Operating Voltage:

1.76 ac volts single component single primary

Special Features:

Weapon system essential

Test Data Document:

28528-1135562 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0