

View Online at <https://aerobasegroup.com/nsn/5950-01-321-1902>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Frequency Rating:**

1.0 kilohertz single component and 100.0 kilohertz single component

**Winding Shielding Method:**

Internal shield grounded to terminal single component

**Body Length:**

0.510 inches

**Overall Diameter:**

0.525 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**End Application:**

Central office, telephone auto

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Features Provided:**

Tinned wire leads

**Winding Operating Current:**

150.0 milliamperes dc single component single secondary

**Dc Resistance Rating In Ohms:**

35.000 single component single primary

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

1.76 ac volts single component single primary

**Special Features:**

Weapon system essential

**Test Data Document:**

28528-1135562 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

7 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0