

View Online at <https://aerobasegroup.com/nsn/5950-01-321-1907>

Reliability Indicator:

Not established

Overall Length:

3.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.437 inches single mounting facility single center group and 2.563 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Overall Height:

Between 2.437 inches and 2.563 inches

Overall Width:

Between 2.687 inches and 2.813 inches

Mounting Slot Width:

0.125 inches single group and 0.251 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

390.0 milliamperes ac single component single secondary

Winding Power Rating:

44.8 volts-amperes single component single secondary

Winding Operating Voltage:

230.00 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0