

View Online at <https://aerobasegroup.com/nsn/5950-01-321-2848>

Reliability Indicator:

Not established

Overall Length:

5.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.552 inches single mounting facility single center group and 3.572 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.540 inches single mounting facility single center group and 2.560 inches single mounting facility single center group

Overall Height:

5.880 inches

Frequency Rating:

181.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta and delta-wye

Winding Shielding Method:

Internal shield grounded to core single component

Body Width:

3.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 primary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

350.0 milliamperes ac single component all secondary

Winding Operating Voltage:

22.00 dc kilovolts single component all secondary

Test Data Document:

82577-984743 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

3 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0