# NSN 5950-01-321-6175

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-321-6175

## Reliability Indicator:

Not established

#### **Overall Length:**

2.420 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.740 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.650 inches single mounting facility single center group

#### **Overall Height:**

3.313 inches

#### **Overall Width:**

2.010 inches

#### Mounting Slot Width:

0.270 inches single group

#### Frequency Rating:

47.0 hertz single component and 400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### Maximum Transformer Power Rating:

2.0 volt-ampere single component

### End Application:

5895-01-280-3568, communication system

#### Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Flange single group and slot single group

#### Winding Function And Quantity:

1 secondary single component

#### Winding Operating Current:

60.0 amperes ac single component single primary

#### **Special Features:**

Primary rated but not included

#### **Terminal Type And Quantity:**

2 threaded stud

Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5950-01-321-6175

Current Transformer - Page 2 of 2

**Fiig:** A058b0

