NSN 5950-01-321-8961

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-321-8961

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus proof and salt spray proof

Overall Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.938 inches single mounting facility single center group

Overall Width:

1.500 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded single component

Body Height:

1.310 inches

Maximum Operating Temp:

125.0 degrees celsius

End Application:

5825-01-055-6064, transponder set operating

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

272.0 milliamperes ac single component single secondary

Winding Operating Voltage:

2.72 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

NSN 5950-01-321-8961

Current Transformer - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0