

View Online at <https://aerobasegroup.com/nsn/5950-01-322-1686>

Reliability Indicator:

Not established

Overall Length:

1.563 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.109 inches single mounting facility single center group and 1.141 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.797 inches single mounting facility single center group and 0.829 inches single mounting facility single center group

Overall Height:

1.375 inches

Overall Width:

1.250 inches

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component or 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Operating Current:

0.2 amperes ac single component single primary output

Winding Operating Voltage:

120.00 ac pounds per hour wet single component single primary input

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0