NSN 5950-01-322-7945

Reactor-transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-322-7945

| Reliability indicator: |
|---|
| Not established |
| Overall Length: |
| 3.309 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.866 inches single mounting facility single center group and 2.886 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.625 inches single mounting facility single center group |
| Overall Height: |
| 5.380 inches |
| Overall Width: |
| 2.290 inches |
| Inductance Rating: |
| 1.26 millihenries single component single winding |
| Frequency Rating: |
| 380.0 hertz 2nd component and 420.0 hertz 2nd component |
| Input-output Phase Relationship: |
| Three phase to three phase 2nd component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Function And Quantity: |
| 1 primary 2nd component and 1 secondary 2nd component |
| Features Provided: |
| Tinned wire leads and color coded lead |
| Thread Size: |
| 0.250 inches single group |
| Winding Operating Current: |
| 8700.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 199.20 ac volts single component single primary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 8 wire lead |
| Shelf Life: |
| N/a |

NSN 5950-01-322-7945

Reactor-transformer - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0