

View Online at <https://aerobasegroup.com/nsn/5950-01-323-1671>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.250 inches single mounting facility single center group

**Overall Height:**

6.500 inches

**Frequency Rating:**

47.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component and internal shield grounded to inclosure and core and brought out to terminal single component

**End Application:**

3610-01-256-0545, phototypesetter

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and slot single group

**Winding Function And Quantity:**

2 primary single component and 6 secondary single component

**Winding Operating Current:**

5.0 amperes dc single component 1st secondary

**Winding Operating Voltage:**

38.00 ac volts single component 2nd secondary

**Special Features:**

2 primary windings; 6 secondary windings; all secondary currents are rectified dc

**Terminal Type And Quantity:**

19 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0