NSN 5950-01-323-1672

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-323-1672

Reliability Indicator:

Not established

Overall Length:

Between 1.770 inches and 1.830 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.400 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.400 inches single mounting facility single center group

Overall Height:

1.650 inches

Overall Width:

Between 1.770 inches and 1.830 inches

Frequency Rating:

167.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

Tinned wire leads

Thread Size:

0.112 inches single group

Winding Operating Current:

111.8 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

57.40 ac volts single component 2nd secondary

Special Features:

First secondary winding has a tap on each terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 pin

Shelf Life:

N/a

NSN 5950-01-323-1672

Power Transformer - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0