

View Online at <https://aerobasegroup.com/nsn/5950-01-323-4882>

Reliability Indicator:

Not established

Overall Length:

2.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.438 inches single mounting facility single center group

Overall Height:

3.120 inches

Overall Width:

2.060 inches

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

20.0 volt-ampere single component

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Tinned wire leads

Thread Size:

0.138 inches single group

Winding Operating Current:

0.3 amperes ac single component single secondary

Winding Power Rating:

7.0 volts-amperes single component single primary

Criticality Code Justification:

Feat

Winding Operating Voltage:

440.00 ac volts single component single primary

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L04292; for navy nuclear propulsion plant products only; terminals4 and 5 connected, terminals6 and 7 connected

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 wire hook and 2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0